



**FORGED AUTOMOTIVE RACING PISTONS • SPORT COMPACT SERIES**

**Mercedes**

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
<b>EVO 1 M102E23 • 2.3L 16V • Turbo (must use K1 149mm rod. Stock is 145mm)</b>															
KE230M955	95.50	Std.											9550XX	468	
KE230M96	96.00	0.50	80.25	149.00	38.90	57	-10				9.0:1	22mm	9600XX	474	1,P,G
KE230M965	96.50	1.00											9650XX	479	

Optional K1 Rod for M102E23 Series: Part # MBH5866BAGB4-A

**EVO 2 M102E25 • 2.5L 16V • Turbo**

KE228M955	95.50	Std.											9550XX	398	
KE228M96	96.00	0.50	87.20	149.00	34.10	57	-10				9.0:1	22mm	9600XX	406	1, P
KE228M965	96.50	1.00											9650XX	413	

Optional K1 Rod for M102E25 Series: Part # MBH5866BAGB4-A

**Mitsubishi DSM**

**1st Generation 1988-92 • 6-Bolt**

**4G63 2.0L Gen 1 • Lancer EVO 1-3/Eclipse/Galant VR-4**

Includes .200" wall pin

K559M85	85.00 / 3.346	Std.									8.1		8500XX	324	
K559M855	85.50 / 3.366	.020	3.465	5.906	1.378	47	-17	.042	0	9.015	8.2	S709	8550XX	332	1
K559M86	86.00 / 3.386	.040	88	150	35			1.1	0	229	8.3	21mm	8600XX	340	
K559M865	86.50 / 3.405	.060									8.4		8650XX	348	
K560M85	85.00 / 3.346	Std.									8.9		8500XX	343	
K560M855	85.50 / 3.366	.020	3.465	5.906	1.378	47	-10	.042	0	9.015	9.0	S709	8550XX	349	1
K560M86	86.00 / 3.386	.040	88	150	35			1.1	0	229	9.1	21mm	8600XX	361	
K560M865	86.50 / 3.405	.060									9.2		8650XX	369	

**1400HD • 8.5:1 • Includes .225" Wall Tool Steel Pins**

K625M85AP	85.00 / 3.346	Std.									8.4		8500XX	341	
K625M855AP	85.50 / 3.366	.020	3.465	5.906	1.378	47	-14	.042	0	9.015	8.5	S721	8550XX	348	1
K625M86AP	86.00 / 3.386	.040	88	150	35			1.1	0	229	8.6	21mm	8600XX	350	
K625M865AP	86.50 / 3.405	.060									8.7		8650XX	357	
K625M87AP	87.00 / 3.425	.080									8.8		8700XX	369	

**1400HD • 10.5:1 E85 Series • Includes .225" wall Tool Steel Pins**

K662M85AP	85.00 / 3.346	Std.									10.56		8500XX	363	
K662M8525AP	85.25 / 3.356	.010	3.465	5.906	1.378	47	1	.042	0	9.015	10.62	S721	8525XX	367	1
K662M855AP	85.50 / 3.366	.020	88	150	35			1.1	0	229	10.68	21mm	8550XX	370	
K662M86AP	86.00 / 3.386	.040									10.8		8600XX	375	

**4G63 2.0L Gen 1 with 100mm 4G64 Stroker Crank**

Includes .200" wall pin

K571M85	85.00 / 3.346	Std.									8.5		8500XX	284	
K571M855	85.50 / 3.366	.020	3.937	5.906	1.130	47	-21	.042	.012	9.015	8.6	S709	8550XX	289	1
K571M86	86.00 / 3.386	.040	100	150	28.7			1.1	0.3	229	8.7	21mm	8600XX	296	

Optional K1 Rod for 4G63, 1st Generation Series, Light weight: Part # 032CI16150

**Foot Notes (far right column)**

- 1 - Most Wiseco Pistons have offset pins. (Pins must be offset, same as OEM, for quietest operation).
- 3 - Optional pin upgrade available. See page 98 for info.
- P - Piston guided rod, washer required.
- G - Only with 2.5L connecting rods

# Mitsubishi DSM

## 2nd Generation 1993-01\* 7 Bolt

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearnce	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
<b>4G63 2.0L Gen 2 • Eclipse &amp; Talon</b>															
<i>Includes .200" wall pin</i>															
K548M85AP	85.00 / 3.346	Std.									8.1		8500XX	335	
K548M8525AP	85.25 / 3.356	.010									8.15		8525XX	337	
K548M855AP	85.50 / 3.366	.020									8.2		8550XX	343	
K548M86AP	86.00 / 3.386	.040	3.465 88	5.906 150	1.378 35	47	-17	.042 1.1	0 0	9.015 229	8.3	S710 22mm	8600XX	352	1
K548M8625AP	86.25 / 3.396	.050									8.35		8625XX	357	
K548M865AP	86.50 / 3.405	.060									8.4		8650XX	353	
K548M87AP	87.00 / 3.425	.080									8.45		8700XX	360	
K595M85AP	85.00 / 3.346	Std.									8.42		8500XX	336	
K595M8525AP	85.25 / 3.356	.010	3.465 88	5.906 150	1.378 35	47	-14	.042 1.1	0 0	9.015 229	8.46	S625 22mm	8525XX		1, 3
K595M855AP	85.50 / 3.366	.020									8.5		8550XX		
K595M86AP	86.00 / 3.386	.040									8.59		8600XX		
K597M85	85.00 / 3.346	Std.									8.9		8500XX	341	
K597M855	85.50 / 3.366	.020	3.465 88	5.906 150	1.378 35	47	-10	.042 1.1	0 0	9.015 229	9.0	S710 22mm	8550XX	345	1
K597M86	86.00 / 3.386	.040									9.1		8600XX	350	
<b>1400HD • Includes .225" wall Tool Steel Pins</b>															
K626M85AP	85.00 / 3.346	Std.									8.45		8500XX	334	
K626M8525AP	85.25 / 3.356	.010									8.5		8525XX	345	
K626M855AP	85.50 / 3.366	.020									8.55		8550XX	341	
K626M86AP	86.00 / 3.386	.040	3.465 88	5.906 150	1.378 35	47	-14	.042 1.1	0 0	9.015 229	8.6	S722 22mm	8600XX	349	1
K626M8625AP	86.25 / 3.396	.050									8.65		8625XX	358	
K626M865AP	86.50 / 3.405	.060									8.7		8650XX		
K626M87AP	87.00 / 3.425	.080									8.8		8700XX	370	
<b>1400HD • Includes .225" wall Tool Steel Pins</b>															
K656M85AP	85.00 / 3.346	Std.									9.63		8500XX	372	
K656M8525AP	85.25 / 3.356	.010									9.68		8525XX		
K656M855AP	85.50 / 3.366	.020	3.465 88	5.906 150	1.378 35	47	-4.5	.042 1.1	0 0	9.015 229	9.74	S722 22mm	8550XX	380	1
K656M86AP	86.00 / 3.386	.040									9.84		8600XX		
K656M865AP	86.50 / 3.405	.060									9.94		8650XX		
K656M87AP	87.00 / 3.425	.080									10.04		8700XX	401	
Optional K1 Rod for 4G63, 2 Series: Part # 032CJ17150 (5.906" / 150mm)															
<b>4G63 2.0L Gen 2, with 156mm Long Rod (Also fits 100mm 4G64 Stroker Crank with stock length rod)</b>															
<i>Includes .200" wall pins</i>															
K674M85AP	85.00 / 3.346	Std.											8500XX		
K674M8525AP	85.25 / 3.356	.010											8525XX		
K674M855AP	85.50 / 3.366	.020											8550XX		
K674M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.130 28.7	47	-12	.042 1.1	.011- 0.3-	9.015 229	8.5	S782 22mm	8600XX		1
K674M8625AP	86.25 / 3.396	.050											8625XX		
K674M865AP	86.50 / 3.405	.060											8650XX		
K674M87AP	87.00 / 3.425	.080											8700XX		
K675M85AP	85.00 / 3.346	Std.											8500XX		
K675M8525AP	85.25 / 3.356	.010											8525XX		
K675M855AP	85.50 / 3.366	.020											8550XX		
K675M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.130 28.7	47	-4	.042 1.1	.011- 0.3-	9.015 229	9.5	S782 22mm	8600XX		1
K675M8625AP	86.25 / 3.396	.050											8625XX		
K675M865AP	86.50 / 3.405	.060											8650XX		
K675M87AP	87.00 / 3.425	.080											8700XX		
K676M85AP	85.00 / 3.346	Std.											8500XX		
K676M8525AP	85.25 / 3.356	.010											8525XX		
K676M855AP	85.50 / 3.366	.020											8550XX		
K676M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.130 28.7	47	+1.9	.042 1.1	.011- 0.3-	9.015 229	10.5:1	S782 22mm	8600XX		1
K676M8625AP	86.25 / 3.396	.050											8625XX		
K676M865AP	86.50 / 3.405	.060											8650XX		
K676M87AP	87.00 / 3.425	.080											8700XX		



**FORGED AUTOMOTIVE RACING PISTONS • SPORT COMPACT SERIES**



**Mitsubishi DSM (Con. rod small end 1.000" or less)**

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
<b>4G63 2.0L Gen 2, with 150mm Rod with 100mm Stroker Crank</b>															
<i>Includes .200" wall pins</i>															
K596M85AP	85.00 / 3.346	Std.									8.5		8500XX	297	
K596M8525AP	85.25 / 3.356	.010	3.937	5.906	1.130	47	-21	.042	.011-	9.015	8.55	S710	8525XX		1
K596M855AP	85.50 / 3.366	.020	100	150	28.7			1.1	0.3-	229	8.6	22mm	8550XX		
K596M86AP	86.00 / 3.386	.040									8.7		8600XX	316	
K674M85AP	85.00 / 3.346	Std.											8500XX		
K674M8525AP	85.25 / 3.356	.010											8525XX		
K674M855AP	85.50 / 3.366	.020											8550XX		
K674M86AP	86.00 / 3.386	.040	3.937	5.906	1.130	47	-12	.042	.011-	9.015	9.7	S782	8600XX		1
K674M8625AP	86.25 / 3.396	.050	100	150	28.7			1.1	0.3-	229		22mm	8625XX		
K674M865AP	86.50 / 3.405	.060											8650XX		
K674M87AP	87.00 / 3.425	.080											8700XX		
K675M85AP	85.00 / 3.346	Std.											8500XX		
K675M8525AP	85.25 / 3.356	.010											8525XX		
K675M855AP	85.50 / 3.366	.020											8550XX	343	
K675M86AP	86.00 / 3.386	.040	3.937	5.906	1.130	47	-4	.042	.011-	9.015	10.8	S782	8600XX		1
K675M8625AP	86.25 / 3.396	.050	100	150	28.7			1.1	0.3-	229		22mm	8625XX		
K675M865AP	86.50 / 3.405	.060											8650XX		
K675M87AP	87.00 / 3.425	.080											8700XX		
K676M85AP	85.00 / 3.346	Std.											8500XX		
K676M8525AP	85.25 / 3.356	.010											8525XX		
K676M855AP	85.50 / 3.366	.020											8550XX		
K676M86AP	86.00 / 3.386	.040	3.937	5.906	1.130	47	+1.9	.042	.011-	9.015	12	S782	8600XX	348	1
K676M8625AP	86.25 / 3.396	.050	100	150	28.7			1.1	0.3-	229		22mm	8625XX		
K676M865AP	86.50 / 3.405	.060											8650XX		
K676M87AP	87.00 / 3.425	.080											8700XX		

Optional K1 Rod for 4G63 Gen. 2 Series: Part # 032CJ17150 (5.906" / 150mm)

**4G64 DSM • 1990-1999**

*4G64 with 4G63 Head (21mm pin) 1988-92*

K564M87	87.00 / 3.425	.020	3.937	5.906	1.378	47	-22	.042	0	9.251	8.9	S624	8700XX	336	1, 3
			100	150	35			1.1	0	235		21mm			
<b>(22mm pin) 1993-05 (Valve pocket compatible with 1999 and later)</b>															
K548M865AP	86.50 / 3.405	Std.	3.937	5.906	1.378	47	-17	.042	0	9.251	9.35	S710	8650XX	353	1
K548M87AP	87.00 / 3.425	.020	100	150	35			1.1	0	235	9.45	22mm	8700XX	360	
<b>(21mm pin) 1988-92 • 1400HD Includes .225" tool steel pins</b>															
K625M865AP	86.50 / 3.405	Std.	3.937	5.906	1.378	47	-14	.042	0	9.251	9.7	S721	8650XX	357	1
K625M87AP	87.00 / 3.425	.020	100	150	35			1.1	0	235	9.8	21mm	8700XX	369	
<b>(22mm pin) 1993-05 • 1400HD Includes .225" wall tool steel pins</b>															
K626M865AP	86.50 / 3.405	Std.	3.937	5.906	1.378	47	-14	.042	0	9.251	9.7	S722	8650XX	356	1
K626M87AP	87.00 / 3.425	.020	100	150	35			1.1	0	235	9.8	22mm	8700XX	369	

**Foot Notes (far right column)**

- 1 - Most Wiseco Pistons have offset pins. (Pins must be offset, same as OEM, for quietest operation).
- 3 - Optional pin upgrade available. See page 98 for info.

**Mitsubishi EVO** (Con. rod small end 1.000" or less)**4G63 Evo 4 - 9**

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
<b>1400H.D. • 9:1cr • Includes .225" wall Tool Steel Pins</b>															
K626M85AP	85.00 / 3.346	Std.									8.9		8500XX	334	
K626M8525AP	85.25 / 3.356	.010									8.95		8525XX	345	
K626M855AP	85.50 / 3.366	.020									9.0		8550XX	341	
K626M86AP	86.00 / 3.386	.040	3.465 88	5.906 150	1.378 35	43	-14	.034 0.86	0 0	9.015 229	9.1	S722 22mm	8600XX	349	1
K626M8625AP	86.25 / 3.396	.050									9.15		8625XX		
K626M865AP	86.50 / 3.405	.060									9.2		8650XX	356	
K626M87AP	87.00 / 3.425	.080									9.3		8700XX	369	
<b>HD2 Asymmetric Skirt • 9.5:1 • Includes .200" wall Pins.</b>															
K666M85AP	85.00 / 3.346	Std.											8500XX	345	
K666M8525AP	85.25 / 3.356	.010									-9.3		8525XX	347	
K666M855AP	85.50 / 3.366	.020									-9.5		8550XX	342	
K666M86AP	86.00 / 3.386	.040	3.465 88	5.906 150	1.373 34.875	43	-10.2	.034 .86	.005- 0.18-	9.015 229	9.5	S782 22mm	8600XX	353	1
K666M865AP	86.50 / 3.405	.060					-10.8						8650XX	360	
K666M8675AP	86.75 / 3.405	.060					-11.1						8700XX	363	
K666M87AP	87.00 / 3.425	.080					-11.4						8700XX		
<b>1400H.D. • E85 Series • 10.5:1cr • Includes .225" wall Tool Steel Pins</b>															
K656M85AP	85.00 / 3.346	Std.									10.49		8500XX	372	
K656M8525AP	85.25 / 3.356	.010									10.54		8525XX		
K656M855AP	85.50 / 3.366	.020									10.6		8550XX	380	
K656M86AP	86.00 / 3.386	.040	3.465 88	5.905 150	1.378 35	43	-4.5	.034 0.86	0 0	9.015 229	10.72	S722 22mm	8600XX		1
K656M865AP	86.50 / 3.405	.060									10.82		8650XX		
K656M87AP	87.00 / 3.425	.080									10.94		8700XX		
<b>HD2 10.5:1 • Asymmetric Skirt • Gas Ported • .225" wall Tool Steel Pins</b>															
K668M85AP	85.00 / 3.346	Std.											8500XX	333	
K668M8525AP	85.25 / 3.356	.010									-2.75		8525XX	336	
K668M855AP	85.50 / 3.366	.020									-3.25		8550XX	339	
K668M86AP	86.00 / 3.386	.040	3.465 88	5.906 150	1.373 34.875	43	-3.9	.034 .86	.005- 0.18-	9.015 229	10.5	S734 22mm	8600XX	345	1
K668M865AP	86.50 / 3.405	.060					-4.5						8650XX	348	
K668M8675AP	86.75 / 3.415	.070					-4.75						8700XX	350	
K668M87AP	87.00 / 3.425	.080					-5						8700XX	352	
<b>NEW! 1400HD Stock Stroke • 156mm Rod • 8:1cr • Includes .225" wall Tool Steel Pins</b>															
K627M85AP	85.00 / 3.346	Std.									8.0		8500XX	292	
K627M8525AP	85.25 / 3.356	.010									8.1		8525XX	294	
K627M855AP	85.50 / 3.366	.020									8.17		8550XX	299	
K627M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.137 28.875	43	-21	.034 0.86	.011- 0.3-	9.015 229	8.2	S722 22mm	8600XX	305	1
K627M8625AP	86.25 / 3.396	.050									8.26		8625XX	307	
K627M87AP	87.00 / 3.425	.080									8.3		8700XX	324	
K627M875AP	87.50 / 3.445	.100									8.4		8750XX	331	
<b>NEW! HD2 Asymmetric Skirt • 156mm Rod • 8.4:1cr • Includes .200" wall Pins</b>															
K667M85AP	85.00 / 3.346	Std.											8500XX	317	
K667M8525AP	85.25 / 3.356	.010									-17		8525XX	320	
K667M855AP	85.50 / 3.366	.020									-17.3		8550XX	322	
K667M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.137 28.875	43	-17.7	.034 0.86	.005- 0.18-	9.015 229	8.4	S782 22mm	8600XX	331	1
K667M865AP	86.50 / 3.405	.060					-18.4						8650XX	340	
K667M8675AP	86.75 / 3.405	.060					-19.1						8700XX	341	
K667M87AP	87.00 / 3.425	.080					-19.4						8700XX	347	
<b>NEW! HD2 Asymmetric Skirt • 156mm Rod • Gas Ported • 9.2:1cr • .225" wall Tool Steel Pins</b>															
K669M85AP	85.00 / 3.346	Std.											8500XX	311	
K669M8525AP	85.25 / 3.356	.010									-10		8525XX	315	
K669M855AP	85.50 / 3.366	.020									-10.25		8550XX	317	
K669M86AP	86.00 / 3.386	.040	3.465 88	6.142 156	1.137 28.875	43	-10.5	.034 0.86	.005- 0.18-	9.015 229	9.2	S734 22mm	8600XX	331	1
K669M865AP	86.50 / 3.405	.060					-11.25						8650XX	332	
K669M8675AP	86.75 / 3.415	.070					-11.75						8700XX	336	
K669M87AP	87.00 / 3.425	.080					-12.25						8700XX	340	



**FORGED AUTOMOTIVE RACING PISTONS • SPORT COMPACT SERIES**

**Mitsubishi EVO (Con. rod small end 1.000" or less)**

**4G63 Evo 4 - 9**

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
<b>NEW! HD2 Asymmetric Skirt • 94mm Stroker • 153mm Rod • 9.3:1cr • Includes .200" wall Pins</b>															
K667M85AP	85.00 / 3.346	Std.					-17						8500XX	317	
K667M8525AP	85.25 / 3.356	.010					-17.3						8525XX	320	
K667M855AP	85.50 / 3.366	.020					-17.7						8550XX	322	1
K667M86AP	86.00 / 3.386	.040	3.700	6.023	1.137	43	-18.4	.034	.005-	9.015	9.3	S782	8600XX	331	
K667M865AP	86.50 / 3.405	.060	94	153	28.875		-19.1	0.86	0.18-	229		22mm	8650XX	340	
K667M8675AP	86.75 / 3.405	.060					-19.4						8700XX	341	
K667M87AP	87.00 / 3.425	.080					-19.8						8700XX	347	

<b>NEW! HD2 Asymmetric Skirt • 94mm Stroker • 153mm Rod • 10.5:1cr • .225" wall Tool Steel Pins</b>															
K669M85AP	85.00 / 3.346	Std.					-10						8500XX	311	
K669M8525AP	85.25 / 3.356	.010					-10.25						8525XX	315	
K669M855AP	85.50 / 3.366	.020					-10.5						8550XX	317	1
K669M86AP	86.00 / 3.386	.040	3.700	6.023	1.137	43	-11.25	.034	.005-	9.015	10.1	S734	8600XX	331	
K669M865AP	86.50 / 3.405	.060	94	153	28.875		-11.75	0.86	0.18-	229		22mm	8650XX	332	
K669M8675AP	86.75 / 3.415	.070					-12.25						8700XX	336	
K669M87AP	87.00 / 3.425	.080					-12.50						8700XX	340	

<b>NEW! 1400HD 94mm Stroker • 153mm Rod • 8.8:1cr • Includes .225" wall Tool Steel Pins</b>															
K627M85AP	85.00 / 3.346	Std.											8500XX	292	
K627M8525AP	85.25 / 3.356	.010											8525XX	294	
K627M855AP	85.50 / 3.366	.020											8550XX	299	1
K627M86AP	86.00 / 3.386	.040	3.700	6.023	1.130	43	-21	.034	.011-	9.015	8.8	S722	8600XX	305	
K627M8625AP	86.25 / 3.396	.050	94	153	28.7			0.86	0.3-	229		22mm	8625XX	307	
K627M87AP	87.00 / 3.425	.080											8700XX	324	
K627M875AP	87.50 / 3.445	.100											8750XX	331	

<b>1400HD 100mm Stroker • 9:1cr • Includes .225" wall Pins</b>															
K627M85AP	85.00 / 3.346	Std.									9.05		8500XX	292	
K627M8525AP	85.25 / 3.356	.010									9.1		8525XX	294	
K627M855AP	85.50 / 3.366	.020									9.15		8550XX	299	1
K627M86AP	86.00 / 3.386	.040	3.937	5.906	1.130	43	-21	.034	.011-	9.015	9.2	S722	8600XX	305	
K627M8625AP	86.25 / 3.396	.050	100	150	28.7			0.86	0.3-	229		22mm	8625XX	307	
K627M87AP	87.00 / 3.425	.080									9.25		8700XX	324	
K627M875AP	87.50 / 3.445	.100									9.4		8750XX	331	
											9.49				

<b>HD2 Asymmetric Skirt • 100mm Stroker • 9.5:1cr • Includes .200" wall Pins</b>															
K667M85AP	85.00 / 3.346	Std.					-17						8500XX	317	
K667M8525AP	85.25 / 3.356	.010					-17.3						8525XX	320	
K667M855AP	85.50 / 3.366	.020					-17.7						8550XX	322	1
K667M86AP	86.00 / 3.386	.040	3.937	5.906	1.137	43	-18.4	.034	.005-	9.015	9.5	S782	8600XX	331	
K667M865AP	86.50 / 3.405	.060	100	150	28.875		-19.1	0.86	0.18-	229		22mm	8650XX	340	
K667M8675AP	86.75 / 3.405	.060					-19.4						8700XX	341	
K667M87AP	87.00 / 3.425	.080					-19.8						8700XX	347	

<b>HD2 Asymmetric Skirt • 100mm Stroker • 10.5:1 • Gas Ported • .225" wall Tool Steel Pins</b>															
K669M85AP	85.00 / 3.346	Std.					-10						8500XX	311	
K669M8525AP	85.25 / 3.356	.010					-10.25						8525XX	315	
K669M855AP	85.50 / 3.366	.020					-10.5						8550XX	317	1
K669M86AP	86.00 / 3.386	.040	3.937	5.906	1.137	43	-11.25	.034	.005-	9.015	10.5	S734	8600XX	331	
K669M865AP	86.50 / 3.405	.060	100	150	28.875		-11.75	0.86	0.18-	229		22mm	8650XX	332	
K669M8675AP	86.75 / 3.415	.070					-12.25						8700XX	336	
K669M87AP	87.00 / 3.425	.080					-12.50						8700XX	340	

**4G64 Evo 4 - 9**

<b>1400HD 100mm Stroker • 9:1cr • Includes .225" wall Tool Steel Pins</b>															
K627M865AP	86.50 / 3.405	Std.									9.25		8650XX	292	
K627M87AP	87.00 / 3.425	.010									9.4		8700XX	294	1
K627M875AP	87.50 / 3.445	.040	3.937	6.142	1.130	43	-21	.034	.011-	9.251	9.49	S722	8750XX	299	
			100	156	28.7			0.86	0.3-	235		22mm			

<b>HD2 Asymmetric Skirt • 100mm Stroker • 10.5:1cr • Gas Ported • .225" wall Tool Steel Pins</b>															
K669M865AP	86.50 / 3.405	Std.					-11.75						8650XX	311	
K669M8675AP	86.75 / 3.415	.010					-12.25						8700XX	315	1
K669M87AP	87.00 / 3.425	.020	3.937	6.142	1.137	43	-12.50	.034	.005-	9.251	10.5	S734	8750XX	317	
			100	156	28.875			0.86	0.18-	235		22mm			

**Foot Notes (far right column)**

1 - Most Wiseco Pistons have offset pins. (Pins must be offset, same as OEM, for quietest operation).

3 - Optional pin upgrade available. See page 98 for info.





# Mitsubishi EVO

## 4G64 with 4G63 DSM head

<b>K548M865AP</b>	86.50 / 3.405	Std.	3.937	5.906	1.378	43	-17	.042	0	9.251	9.8	S710	8650XX	353	1
<b>K548M87AP</b>	87.00 / 3.425	.020	100	150	35			1.1	0	235	9.9	22mm	8700XX	360	

Includes .200" wall pin

<b>K626M865AP</b>	86.50 / 3.405	Std.	3.937	5.906	1.378	43	-14	.042	0	9.251	10.3	S722	8650XX	356	1
<b>K626M87AP</b>	87.00 / 3.425	.020	100	150	35			1.1	0	235	10.4	22mm	8700XX	360	

Includes .225" wall tool steel pin

## HD2 Asymmetric Skirt • EVO 4G64 • Includes .200" wall Pins.

<b>K666M865AP</b>	86.50 / 3.405	Std.	3.937	5.906	1.373	43	-10.8	.042	.0035	9.251	10.7	S782	8650XX	360	1
<b>K666M8675AP</b>	86.75 / 3.415	.010	100	150	34.875		-11.1	1.1	0.09	235		22mm	8700XX	363	
<b>K666M87AP</b>	87.00 / 3.425	.020					-11.4						8700XX	360	

## HD2 Asymmetric Skirt • Gas Ported • .225" wall tool steel Pins.

<b>K668M865AP</b>	86.50 / 3.405	Std.	3.937	5.906	1.373	43	-4.5	.042	.0035	9.251	11.8	S734	8650XX	348	1
<b>K668M8675AP</b>	86.75 / 3.415	.010	100	150	34.875		-4.75	1.1	0.09	235		22mm	8700XX	350	
<b>K668M87AP</b>	87.00 / 3.425	.020					-5						8700XX	352	

Optional K1 Rod for 4G63, 2nd Generation Series: Part # 032CJ17150

Optional K1 4G63 Crank \* 4340 Billet

Part # 032BCJ880 88mm Stroke

Part # 032BCJ940 94mm Stroke (For Stroker Custom Piston only)

Part # 032BCJ100 100mm Stroke

All have: 7-Bolt Flanges \* 4G63 Main & Rod Journals \* 31 lbs.

## Evo 10

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
------------	----------------	------------	--------	-----------	----------	-----------	-----------	----------------	----------------	-----------	-------------	-----------------------	-------------------	------	------------

### 4B11T Evo X 2008+

<b>K636M86</b>	86.00 / 3.386	Std.									9.2		8600XX	371	1
<b>K636M865</b>	86.50 / 3.405	.020	3.386	5.659	1.309	49	-4.5	.048	0	8.661	9.3	S752	8650XX	379	
<b>K636M87</b>	87.00 / 3.425	.040	86	143.75	33.25			1.2	0	220	9.4	23mm	8700XX	382	
<b>K636M88</b>	88.00 / 3.464	.080									9.6		8800XX	395	

Optional K1 Rod for Mitsubishi Evo 10 4B11T: Part # 032CK21144

## 420A

### 420A Eclipse 2.0L 16V DOHC 1995-02 (Same as Neon DOHC engine)

<b>K580M875</b>	87.50 / 3.445	Std.	3.268	5.472	1.236	52	-5	.040	.004-	8.346	8.8	S624	8750XX	331	1, 3
<b>K580M88</b>	88.00 / 3.464	.020	83	139	31.4			1	0.1-	212	8.9	21mm	8800XX	339	
<b>K580M885</b>	88.50 / 3.484	.040									9.0		8850XX	347	
<b>K581M875</b>	87.50 / 3.445	Std.	3.268	5.472	1.236	52	5	.040	.004-	8.346	10.3	S624	8750XX	334	1, 3
<b>K581M88</b>	88.00 / 3.464	.020	83	139	31.4			1	0.1-	212	10.4	21mm	8800XX	341	
<b>K581M885</b>	88.50 / 3.484	.040									10.5		8850XX	349	

### 4G54B Starion Conquest TSI 2.5L 16V 1984-89

<b>K555M92</b>	92.00 / 3.622	.031	3.858	6.535	1.390	73.5	-17	.052	.028-	9.882	7.2	S625	9200XX	382	1, 3
<b>K555M925</b>	92.50 / 3.642	.051	98	166	35.3			1.3	0.7-	251	7.3	22mm	9250XX	396	

## NEW! 4G93 & 4G94

### 4G93 1.8L 1997-02 Mirage / Lancer

<b>K683M815AP</b>	81.50 / 3.209	.020	3.504	5.250	1.190	47	-2.5 FT	.042	.027-	8.219	8.9	S622	8150XX		1, 3
<b>K683M82AP</b>	82.00 / 3.228	.040	89	133.25	30.25			1.07	.68-	208.75	9.0	19mm	8200XX		

Optional K1 Rod for Mitsubishi 4G93: Part # 032CN12133

### 4G94 2.0L 2002-05 Lancer

<b>K683M815AP</b>	81.50 / 3.209	Std.	3.770	6.023	1.190	49	-2.5 FT	.042	.036-	9.134	9.06	S622	8150XX		1, 3
<b>K683M82AP</b>	82.00 / 3.228	.020	95.8	153	30.25			1.07	0.91	231	9.15	19mm	8200XX		

Optional K1 Rod for Mitsubishi 4G94: Part # 032CM12153

### 6G72T 3.0L 24V 3000GT

<b>K570M915</b>	91.50 / 3.602	.015	2,991	5.548	1,250	48	-14	.050	.019-	8.313	7.8	S625	9150XX	343	1, 3
<b>K570M92</b>	92.00 / 3.622	.035	76	140.9	31.75			1.27	0.48-	211.15	7.85	22mm	9200XX	355	
<b>K570M925</b>	92.50 / 3.642	.055									7.9		9250XX	362	